



STEAM QM[®]-3 INSTALLATION DETAILS FORM (IDF)

Section 1 – Ordering Processing/Tracking Detail:

Complete this page and submit with orders of complete units to domsales@armstronginternational.com

Point of Order / Sold To: _____ (eg: ABC Mechanical)

City: _____ State: _____ Rep Firm: _____

Point of Installation: _____ (eg: Heinz Ketchup)

City: _____ State: _____ Rep Firm: _____

Point of Specification: _____ (eg: DEF Consulting Engineers)

City: _____ State: _____ Rep Firm: _____

Other Influence: _____ (eg: Source of Recommendation)

Section 2 – Technical Detail:

Calormieter Orientation: Horizontal Vertical

Equipment Type: _____

Steam generated from purified water: Yes No

Operating Steam Pressure: _____ PSI

Number of wall mount brackets needed: _____

Utilities available at installation location: *(Cabinet must be mounted within 3 meters (79 in.) of the calorimeter and in a secure and level position)*

Steam Mesurement point (1/4" or 1-1/2" sanitary fitting): Yes No

Water Supply (1-5 bar): Yes No

Power Supply: 115 Volts 230 Volts

Communication: Local Display Modbus (BAS/DCS) w/ Data Logger Modbus w/ Armstrong supplied Data Logger

Section 3

Service Contract Desired: Yes No

EN 285 Regulated: Yes No

List any non-standard options or details here:
