

# DIMENSIONS & DATA CERTIFIED FOR:

Representative:

Order:

Customer:

Order:

Project:

Requirements:

By:

Date:

## LIST OF MATERIALS:

NAME OF PART	MATERIAL
CAP & BODY	ASTM A240 T304L SS
VALVE SEAT/VALVE	17-4PH H900
FLOAT	ASTM A167 T304 SS
ADAPTER PLATE	ASTM A240 T304 SS
GUIDE PLATE ASS'Y	
LEVER ASS'Y	

## TECHNICAL INFORMATION


MODEL NO.	13 AV/LD	22 LD/AV
PIPE CONNECTIONS	1" NPT [DN25] & 1" SW	3/4 NPT [DN20]   3/4 SW
"A" (BODY DIA.)	4-1/2 [114]	3-7/8 [98]
"B" (HEIGHT)	11-3/8 [289]	8-23/32[221.2]   8-13/32[213.6]
"D" (BOTTOM TO $\phi$ INLET)	6-1/8 [155]	3-3/8 [86]
"K" ( $\phi$ OF TRAP TO $\phi$ OUTLET)	1-3/16 [30]	15/16 [24]
"L" ( $\phi$ OF TRAP TO INLET)	3-9/32 [83]	2-5/8 [67]
WEIGHT	7-1/2 lbs[3.4 kgs]	3-3/4 lbs [1.7 kgs]

## DESIGN INFORMATION

MAX. ALLOWABLE PRESSURE (VESSEL DESIGN)	570 psig @ 100°F [39 bar @ 38°C]	600 psig @ 100°F [41 bar @ 38°C]
	490 psig @ 500°F [34 bar @ 260°C]	475 psig @ 500 °F [33 bar @ 260°C]

### MODEL TYPE

<input type="checkbox"/>	13 AV
<input type="checkbox"/>	13 LD
<input type="checkbox"/>	22 LD
<input type="checkbox"/>	22 AV



Product

13 AV/LD  
22 LD/AV

ENGLISH

CD No.

1086

Date

2/11/09

Current CN21600

WEB Y|N  
✓

Rev; D

sht. 1

By; paulg